

EPDM Gauge Guards



BioPure Gauge Guard

Features and benefits

- Available in silicone or EPDM
- USP Class VI compliant and Animal Derived Component Free (ADCF)
- Compliant with FDA regulations CFR 21 177.2600
- Lot numbering enables product traceability
- Irradiated EPDM gaskets available on request







Technical specifications

	EPDM Gauge Guards
Gasket type	Isolator
Internal diameter	9.65 - 35.56 mm (0.38 - 1.4 in)
External diameter	21.59 - 50.29 mm (0.85 - 1.98 in)
Size	0.5, 0.75, 1, 1.5 in
Quantity	25 PCS
Certification and compliance	ADCF, USP Class VI
Operating temperature	-57 °C to 154 °C (-70 °F to 310 °F)
Shelf life	5 years

Materials of construction

	EPDM Gauge Guards
Material	EPDM

EPDM Gauge Guards dimensions



	Size	ID (in)	OD (in)
S	0.5	0.38	0.85
	0.75	0.63	0.85
L	1	0.9	1.98
	1.5	1.4	1.98

Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the user's responsibility to ensure product suitability for use within their application. Watson-Marlow and WMArchitect are registered trademarks of Watson-Marlow Limited. BioClamp, BioBarb, FlatBioEndCap, BioEndCap, BioValve, BioTube applicator and Q-Clamp are Trademarks of BioPure Technology Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB.



wmfts.com/global
11 July 2025