

# Tube only (TO) grade hoses



Corroflon

## Features and benefits

- Natural or anti-static patented PTFE liner
- The shallow convoluted liner design delivers exceptional flexibility while minimizing restriction in flow rate
- Vacuum and kink resistant
- High temperature and pressure capability
- Chemical resistant
- PTFE lined and non-lined end fittings
- Range of braid, cover and external protection options available

Nominal hose bore size		Bore inside convolutions		Corroflon grade (braid & cover)	Maximum working pressure of hose		Burst pressure		Minimum bend radius	
in	mm	in	mm		bar	psi	bar	psi	in	mm
1/2	15	0.440	11.2	TO	6	87	24	350	1 1/2	38
3/4	20	0.620	15.7	TO	5	70	20	290	2	51
1	25	0.847	21.5	TO	4.5	65	18	260	2 3/4	70
1 1/4	32	1.080	27.5	TO	4	58	16	230	3 1/4	82
1 1/2	40	1.250	32.0	TO	3.5	50	14	205	4	100
2	50	1.690	43.0	TO	3	44	12	175	5 1/2	140
2 1/2	65	2.120	54.0	TO	2.5	36	10	145	7	178
3	80	2.500	64.0	TO	2	29	8	115	9	230
4	100	3.860	98.0	TO	1.5	22	6	87	11 1/4	300
6	150	5.250	130.0	TO	0.75	11	3	44	23 1/4	600

TO = Tube only

## Technical specifications

	Tube only (TO) grade hoses
Nominal bore size	0.5 - 6 in (15 - 150 mm)
Actual bore size	0.44 - 5.25 in (11.2 - 130 mm)
Length	13 - 72 ft (4 - 22 m)
Outside diameter	0.63 - 5.75 in (16.1 - 146 mm)
Max. operating pressure	87 psi (6 bar)
Burst pressure	44 - 350 psi (3 - 24 bar)
Certification and compliance	(EU) 10/2011, 3.1 Traceability, ATEX, EN16643:2016, FDA (materials), ISO 14001:2015, ISO 9001:2015, OHSAS 18001:2015
Bend radius	1.5 - 23.75 in (38 - 600 mm)
Weight per unit length	0.14 - 4.36 lb/ft (0.21 - 6.5 kg/m)
Braid	None
Cover	None
Hose external protection options	Protection coil, Safeguard, Scuff rings
End fitting	90° elbow fittings, BSP and NPT threaded fittings, CAM and groove fittings, DIN 11851 fittings, JIC fittings, PTFE dip pipe fittings, Sanitary triclamp fittings, SMS and RJT fittings, Swivel flange fittings
Labelling options	Color coding, Standard
Vacuum resistance	Vacuum resistant to -0.9bar up to 150C (302F)

## Materials of construction

	Tube only (TO) grade hoses
Helical wire	Stainless steel
Liner tube	Antistatic PTFE, Natural PTFE
Fitting liner	PTFE

---

Disclaimer: The information contained in this document is believed to be correct but Aflex Hose Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the users' responsibility to ensure product suitability for use within their application. Bioflex, Corroflon, Corroline, Hyperline FX, Pharmaline are registered trademarks of Aflex Hose Limited. A member of Watson-Marlow Fluid Technology Group, A Spirax-Sarco Engineering plc company.



wmfts.com/global  
12 December 2025