

Visiflon Tube only (TO) grade hoses



Visiflon

Features and benefits

- Very flexible and kink resistant
- Temperature resistant
- Chemical resistant

Visiflon Tube only (TO) grade hoses performance

Nominal hose size		*Actual hose bore size		Hose grade	Outside diameter of tube or braid		Minimum bend radius		Maximum working pressure (MWP)		Weight per unit length		Hose part number
in	mm	in	mm		in	mm	in	mm	bar	psi	kg/mtr	lbs/ft	
1/8	10.0	1/8	6.3	TO	0.420	10.70	1	25	4	58	0.057	0.038	71-100-06
1/2	12.0	1/8	9.5	TO	0.555	14.10	1 1/2	38	4	58	0.076	0.051	71-100-08
1/8	16.0	1/2	12.7	TO	0.780	19.80	2	50	4	58	0.126	0.084	71-100-10
1/8	20.0	3/8	16.0	TO	0.835	21.20	3	75	3	43	0.166	0.111	71-100-12
1	25.0	1/2	22.0	TO	1.143	29.00	3 1/2	89	3	43	0.235	0.157	71-100-16
1 1/4	32.0	1 1/8	28.0	TO	1.349	34.20	4	100	2	29	0.342	0.229	71-100-20
1 1/2	40.0	1 3/8	35.0	TO	1.773	45.00	6	150	2	29	0.415	0.278	71-100-24
2	50.0	1 7/8	47.0	TO	2.325	59.00	8	200	2	29	0.631	0.423	71-100-32

*Visiflon Hose assemblies require that the convolutions at the ends of the hose are opened out to accept either Hydraulic or PTFE Tail end fittings.

Technical specifications

	Visiflon Tube only (TO) grade hoses
Nominal bore size	10 - 32 mm (0.375 - 1.25 in)
Actual bore size	6.3 - 28 mm (0.25 - 1.125 in)
Length	15 - 20 m (50 - 70 Ft)
Outside diameter	10.7 - 34.2 mm (0.42 - 1.349 in)
Max. operating pressure	4 bar (58 psi)
Certification and compliance	3.1 Traceability, FDA (materials), TS 16949:2016
Operating temperature	-73 °C to 230 °C (-100 °F to 450 °F)
Bend radius	25 - 100 mm (1 - 4 in)
Weight per unit length	0.057 - 0.342 kg/m (0.0338 - 0.229 lb/ft)
Braid type	None
Cover	None
End fitting	BSP and NPT threaded fittings, Flat Seat Lug Nut Female Unions, JIC fittings, NPT and BSPT fittings, Standpipe Fittings, Tube Fittings
Vacuum resistance	Vacuum resistant to -0.9 bar up to 80 °C (176 °F)

Materials of construction

	Visiflon Tube only (TO) grade hoses
Liner tube	Anti-static PTFE, Natural PTFE

Disclaimer: The information contained in this document is believed to be correct but Aflex Hose Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the user's responsibility to ensure product suitability for use within their application. Bioflex, Corroflon, Corroline, Hyperline FX, Pharmaline are registered trademarks of Aflex Hose Limited. A member of Watson-Marlow Fluid Technology Solutions, A Spirax-Sarco Engineering plc company.



wmfts.com/global
12 December 2025