

Features and benefits

- Lot numbers moulded in for full traceability
- Profiled to minimise flow path turbulence
- Thread pitch is calibrated to 2 mm per turn, permitting controlled flow restriction
- Suitable for sterilisation by autoclave and gamma irradiation
- Moulded from reinforced Nylon USP Class VI



Technical specifications

	BioValve
Max. operating pressure	10 bar (145 psi)
Autoclave stability	121 °C 30 minutes
Gamma stability	Max 40 kGy Cumulative
Shelf life	5 years
Certification and compliance	ADCF, ISO 14644-1 Class 7, ISO 9001, ISO10993, USP Class VI
Size	½-1¼ OD Tube, 1/8-¾ OD Tube in
Quantity	5 PCS

Materials of construction

	BioValve
Material	Glass reinforced Nylon 66

Product codes

Part Number	Size	Material	Max operating pressure		Max Cumulative Gamma Dose
BV0500NW	1/8" - 3/4" - OD Tubing	Nylon 66	150 psiG	10 bar	40 kGy
BV1000NW	1/2" - 1 1/4" - OD Tubing	Nylon 66	150 psiG	10 bar	40 kGy

Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the user's responsibility to ensure product suitability for use within their application. Watson-Marlow and WMArchitect are registered trademarks of Watson-Marlow Limited. BioClamp, BioBarb, FlatBioEndCap, BioEndCap, BioValve, BioTube applicator and Q-Clamp are Trademarks of BioPure Technology Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB.



wmfts.com/global
11 July 2025