

# BioEndCap

BioEndCap



## Features and benefits

- Lot numbers molded in for full traceability
- Unique pull-tab ensures easy removal of the cap
- Suitable for sterilization by autoclave and gamma irradiation



## Technical specifications

	BioEndCap
Max. operating pressure	58 psi (4 bar)
Fluid temperature	40 °F to 104 °F (5 °C to 40 °C)
Operating temperature	23 °F to 104 °F (-5 °C to 40 °C)
Autoclave stability	121 °C 30 minutes
Gamma stability	50kGy
Shelf life	5 years
Certification and compliance	ADCF, ISO 14644-1 Class 7, ISO 9001, ISO10993, USP Class VI
TC Size	½-¾ TC - 1-1½ TC in
Quantity	10 PCS

## Materials of construction

	BioEndCap
Material	Natural PP

## Product codes

Part Number	Size	Flange Size	Material
PEC-500-750	1/2" - 3/4" TC	1/2" - 3/4"	Natural PP
PEC-100-150	1" - 1 1/2" TC	1" - 1 1/2"	Natural PP

Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the user's responsibility to ensure product suitability for use within their application. Watson-Marlow and WMArchitect are registered trademarks of Watson-Marlow Limited. BioClamp, BioBarb, FlatBioEndCap, BioEndCap, BioValve and BioTube applicator are Trademarks of BioPure Technology Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB. Q-Clamp is used under licence.



wmfts.com/global  
11 July 2025