

FlatBioEndCap

FlatBioEndCap



Features and benefits

- Lot numbers moulded in for full traceability
- Suitable for sterilisation by autoclave and gamma irradiation



Technical specifications

	FlatBioEndCap
Max. operating pressure	4 bar (58 psi)
Fluid temperature	5 °C to 40 °C (40 °F to 104 °F)
Operating temperature	-5 °C to 40 °C (23 °F to 104 °F)
Autoclave stability	121 °C 30 minutes
Gamma stability	50 kGy
Shelf life	5 years
Certification and compliance	ADCF, ISO 14644-1 Class 7, ISO 9001, ISO10993, USP Class VI
TC Size	½-¾ TC - 2½ TC in
Quantity	10 PCS

Materials of construction

	FlatBioEndCap
Material	Natural PP

Product codes

Part Number	Size	Flange Size	Material
PPEC05000750FC	1/2" - 3/4" TC	1/2" - 3/4"	Natural PP
PPEC10001500FC	1" - 1 1/2" TC	1" - 1 1/2"	Natural PP
PPEC2000FC	2" TC	2"	Natural PP
PPEC2500FC	2 1/2" TC	2 1/2"	Natural PP

Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the user's responsibility to ensure product suitability for use within their application. Watson-Marlow and WMArchitect are registered trademarks of Watson-Marlow Limited. BioClamp, BioBarb, FlatBioEndCap, BioEndCap, BioValve, BioTube applicator and Q-Clamp are Trademarks of BioPure Technology Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB.



wmfts.com/global
11 July 2025