

Platinum-cured silicone braided hose

Platinum-cured silicone braided hose

Features and benefits

- Manufactured and packed within an ISO 14644 Class 7 cleanroom
- Post sterilized validation to current USP, EU and FDA standards
- Withstands sterilization and repeat autoclave
- Available in either 7.6 m and 15.2 m coils



Technical specifications

	Platinum-cured silicone braided hose
Bore size	0.125 - 1 in (3.2 - 25.4 mm)
External diameter	0.345 - 1.36 in (8.8 - 34.5 mm)
Certification and compliance	ADCF, ISO 10993, ISO Class 7, Ph. Eur. 3.1.9, USP <788>, USP <95>, USP <97>, USP Class VI
Burst pressure	220 - 700 psi (15.1 - 48.3 bar)
Shelf life	5 years
Gamma stability	Max 50kGy
Autoclave stability	Yes

Materials of construction

	Platinum-cured silicone braided hose
Inner tube	Platinum-cured silicone
Braid layer 1	Polyester
Outer tube	Platinum-cured silicone

Product codes

Part number	I.D. mm (inch)	O.D. mm (inch)	Length m (ft)	Min. bend radius mm (inch)	Min. burst pressure at 20C/68F bar (psi)
BPSHP0125-C	3.2 (0.125)	8.8 (0.345)	7.6 (25)	25.4 (1.00)	48.3 (700)
BPSHP0188-C	4.8 (0.187)	10.3 (0.407)	7.6 (25)	31.8 (1.25)	44.3 (650)
BPSHP0250-C	6.4 (0.250)	12.4 (0.490)	7.6 (25)	38.0 (1.5)	43.1 (625)
BPSHP0375-C	9.6 (0.375)	16.7 (0.658)	7.6 (25)	44.4 (1.75)	37.9 (550)
BPSHP0500-C	12.7 (0.500)	20.3 (0.800)	7.6 (25)	50.8 (2.00)	34.5 (500)
BPSHP0625-C	15.9 (0.625)	24.5 (0.965)	7.6 (25)	63.5 (2.5)	28.9 (420)
BPSHP0750-C	19.0 (0.750)	27.9 (1.100)	7.6 (25)	76.2 (3.00)	24.1 (350)
BPSHP0875-C	22.2 (0.875)	32.0 (1.260)	7.6 (25)	88.9 (3.50)	20.7 (300)
BPSHP1000-C	25.4 (1.00)	34.5 (1.360)	7.6 (25)	101.6 (4.00)	15.1 (220)
BPSHP0125-D	3.2 (0.125)	8.8 (0.345)	15.2 (50)	25.4 (1.00)	48.3 (700)
BPSHP0188-D	4.8 (0.187)	10.3 (0.407)	15.2 (50)	31.8 (1.25)	44.3 (650)
BPSHP0250-D	6.4 (0.250)	12.4 (0.490)	15.2 (50)	38.0 (1.5)	43.1 (625)
BPSHP0375-D	9.6 (0.375)	16.7 (0.658)	15.2 (50)	44.4 (1.75)	37.9 (550)
BPSHP0500-D	12.7 (0.500)	20.3 (0.800)	15.2 (50)	50.8 (2.00)	34.5 (500)
BPSHP0625-D	15.9 (0.625)	24.5 (0.965)	15.2 (50)	63.5 (2.5)	28.9 (420)
BPSHP0750-D	19.0 (0.750)	27.9 (1.100)	15.2 (50)	76.2 (3.00)	24.1 (350)
BPSHP0875-D	22.2 (0.875)	32.0 (1.260)	15.2 (50)	88.9 (3.50)	20.7 (300)
BPSHP1000-D	25.4 (1.00)	34.5 (1.360)	15.2 (50)	101.6 (4.00)	15.1 (220)

Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the user's responsibility to ensure product suitability for use within their application. Watson-Marlow and WMArchitect are registered trademarks of Watson-Marlow Limited. BioClamp, BioBarb, FlatBioEndCap, BioEndCap, BioValve and BioTube applicator are Trademarks of Technology Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB. Q-Clamp is used under licence.



wmfts.com/global
28 October 2025